


Screw Terminal Board



DB-8225 Screw Terminal Board With CJC

Screw terminal board using 37-pin cable I/O ports for A-82X series and PCI-1800 series
 16-channel single-ended or 8-channel differential
 Blank pads for break detection, low-pass filter, current shut and voltage attenuation
 On board cold junction circuit in analog input channel 1 (Jumper selectable single-ended or differential mode)
 Dimensions: 114 mm x 170 mm


Ordering Information

Standard

DB-8225/1: Screw terminal board with CA-3710 cable
DB-8225/2: Screw terminal board with CA-3720 cable

Optional

CA-3710: 37-pin D-sub cable, 1m
CA-3720: 37-pin D-sub cable, 2m



DB-8125 Screw Terminal Board

DB-8125 is equipped with a DB-37 connector and two 20-pin flat-cable connectors
 Blank pads for break detection, low-pass filter, current shut and voltage attenuation
 Compatible to 880 series daughter board
 Dimensions: 221 mm x 115 mm

Ordering Information

Standard

DB-8125: Screw terminal board with CA-3710 cable

Optional

CA-3710: 37-pin D-sub cable, 1m
CA-2020: 20-pin flat cable, 2m
CA-3720: 37-pin D-sub cable, 2m



DB-1825 Screw Terminal Board

Screw terminal board using 37-pin cable I/O ports for PCI-1802, PCI-1002, PCI-1202, ISO-AD32 series
 32-channel single-ended, 16-channel differential
 Blank pads for break detection, low-pass filter, current shut and voltage attenuation
 Dimensions: 114 mm x 170 mm

Ordering Information

Standard

DB-1825/1: Screw terminal board with CA-3710 cable
DB-1825/2: Screw terminal board with CA-3720 cable

Optional

CA-3710: 37-pin D-sub cable, 1m
CA-3720: 37-pin D-sub cable, 2m



DB-8325 Screw Terminal Board

Screw terminal board using 37-pin cable for ISO-813 or other 813 series boards
 Blank pads for break detection, low-pass filter, current shut and voltage attenuation
 Dimensions: 220 mm x 114 mm

Ordering Information


Standard

DB-8325/1: Screw terminal board with CA-3710 cable
DB-8325/2: Screw terminal board with CA-3720 cable

Optional

CA-3710: 37-pin D-sub cable, 1m
CA-3720: 37-pin D-sub cable, 2m

Screw Terminal Board



DB-8025 Screw Terminal Board

DB-8025 is equipped with two 20-pin flat-cable connectors
Blank pads for break detection, low-pass filter, current shut and voltage attenuation
Compatible to 780 series daughter board
Dimensions: 102 mm x 114 mm

Ordering Information Standard

DB-8025: Screw terminal board with two CA-2010 cable

Optional

CA-2020: 20-pin flat cable, 2m



DB-200

DB-200 is equipped with one 25-pin D-Sub connector and two 9-pin D-Sub connectors
Dimensions: 190 mm x 75 mm

Ordering Information Standard

DB-200: Encoder interface board for SERVO-300 with one CA-0915, CA-2520 cable & CA-0920 cable

Optional

CA-2520: 25-pin Male-Male D-sub flat cable, 2m

CA-0920: 9-pin Male-Male D-sub cable, 2m



DB-8425 Screw Terminal Board

9-pin D-Sub connector pin-to-pin screw terminal for PISO-DA2
Dimensions: 103 mm x 86 mm

Ordering Information Standard

DB-8425: Screw terminal board for PISO-DA2 with two CA-0920 cable

Optional

CA-0920: 9-pin Male-Male D-sub cable, 2m



DB-8R

DB-8R is equipped with one 25-pin D-Sub connector
7-relay output, 8 isolated digital input X, Y limit switch input, emergency input
Dimensions: 190 mm x 105 mm

Ordering Information Standard

DB-8R: Motion interface I/O board with CA-2520 cable

Optional

CA-2520: 25-pin Male-Male D-sub flat cable, 2m



DB-37 Screw Terminal Board

37-pin D-sub connector pin-to-pin screw terminal for any 37-pin D-sub connector of I/O board
Dimensions: 130 mm x 78 mm

Ordering Information Standard

DB-37: Direct connection board



DB-3R

DB-3R is equipped with one 9-pin D-Sub connector and 3-relay outputs
Dimensions: 103 mm x 86 mm

Ordering Information Standard

DB-3R: Daughter board for WDT-03 with one CA-0915 cable

Optional

CA-0915: 9-pin Male-Female D-sub cable, 1.5m