



## PCI-1802LU

Universal PCI, 330kS/s, 32-ch, 12-bit AI Multifunction Board

## PCI-1802HU

Universal PCI, 44k S/s, 32-ch, 12-bit AI Multifunction Board

### Features

- Universal PCI (3.3 V/5 V) Interface
- Supports Card ID (SMD Switch)
- 2-channel, 12-bit Analog Output
- 16-channel 5 V/TTL Digital Output
- 16-channel 5 V/TTL Digital Input
  - ☐ Pull-high and Pull-low Resistors for DI Channels
- 32 Single-ended/16 Differential Analog Input Channels
  - ☐ 12-bit, 330 kS/s or 44 kS/s AD Converter
  - ☐ Built-in MagicScan Controller
  - ☐ Internal Trigger: Software-trigger, Pacer-trigger
  - ☐ External Trigger: Post-trigger, Pre-trigger, Middle-trigger
- High-speed data transfer rate up to 2.7 M words/sec.



### Introduction

The PCI-1802LU/HU card is designed as an easy replacement for the PCI-1802L/H without requiring any modification to the software or the driver.

The PCI-1802LU/HU is a high-performance multifunction card that provides high-speed Analog and Digital I/O functions. The PCI-1802LU/HU is based on the Universal PCI interface, supporting both the 3.3 V and the 5 V PCI bus, and features a continuous 330 kS/s or 44 kS/s 12-bit resolution AD converter, an 8 K-sample hardware FIFO, a MagicScan controller (for multi-channel scanning), a 2-channel 12-bit DA converter, and 16-channel Digital Input and 16-channel Digital Output.

The PCI-1802LU/HU provides either 32-channel single-ended or 16-channel differential Analog Inputs that are jumper selectable, and a programmable high-speed PGA that is equipped for gain controls (0.5/1/2/4/8 for Low Gain, and 0.5/1/5/10/50/100/500/1000 for High Gain).

The PCI-1802LU/HU also includes an onboard Card ID switch and pull-high/low DI resistors. The Card ID enables the board to be recognized via software if two or more PCI-1802LU/HU cards are installed in the same computer. The pull-high/pull-low resistors allow the DI status to be predefined instead of remaining floating if the DI channels are disconnected or interrupted.

### Pin Assignments

| Pin Assignment | Terminal No. | Pin Assignment | Pin Assignment | Terminal No. | Pin Assignment |
|----------------|--------------|----------------|----------------|--------------|----------------|
| AI_0           | 01           | 20 AI_16       | DO 0           | 01           | DO 0           |
| AI_1           | 02           | 21 AI_17       | DO 2           | 03           | DO 2           |
| AI_2           | 03           | 22 AI_18       | DO 4           | 05           | DO 4           |
| AI_3           | 04           | 23 AI_19       | DO 6           | 07           | DO 6           |
| AI_4           | 05           | 24 AI_20       | DO 8           | 09           | DO 8           |
| AI_5           | 06           | 25 AI_21       | DO 10          | 10           | DO 10          |
| AI_6           | 07           | 26 AI_22       | DO 12          | 12           | DO 12          |
| AI_7           | 08           | 27 AI_23       | DO 14          | 14           | DO 14          |
| AI_8           | 09           | 28 AI_24       | GND            | 16           | GND            |
| AI_9           | 10           | 29 AI_25       | +5 V           | 18           | +5 V           |
| AI_10          | 11           | 30 AI_26       |                |              |                |
| AI_11          | 12           | 31 AI_27       |                |              |                |
| AI_12          | 13           | 32 AI_28       |                |              |                |
| AI_13          | 14           | 33 AI_29       |                |              |                |
| AI_14          | 15           | 34 AI_30       |                |              |                |
| AI_15          | 16           | 35 AI_31       |                |              |                |
| A.GND          | 17           | 36 Da2 out     |                |              |                |
| Da1 out        | 18           | 37 D.GND       |                |              |                |
| Ext_Trg        | 19           |                |                |              |                |

### Software

| Drivers                             |                                                         |
|-------------------------------------|---------------------------------------------------------|
| <input checked="" type="checkbox"/> | 32/64-bit Windows 10/11                                 |
| <input checked="" type="checkbox"/> | Linux                                                   |
| <input checked="" type="checkbox"/> | DASYLab                                                 |
| Sample Programs                     |                                                         |
| <input checked="" type="checkbox"/> | DOS Lib and TC/BC/MSC Demo                              |
| <input checked="" type="checkbox"/> | VB/VC/Delphi/VB.NET/C#.NET/VC.NET/LabVIEW/Python/MATLAB |

### Applications

- High speed data acquisition system
- Process monitor and control.
- Vibration analysis.




### Ordering Information

|                        |                                                                                                             |
|------------------------|-------------------------------------------------------------------------------------------------------------|
| <b>PCI-1802LU CR</b>   | Universal PCI, 330kS/s, 32-ch, 12-bit AI Multifunction Board (RoHS)<br>Includes one CA-4002 D-Sub connector |
| <b>PCI-1802LU/S CR</b> | Universal PCI, 330kS/s, 32-ch, 12-bit AI Multifunction Board (RoHS)<br>Includes one CA-3710 D-Sub cable     |
| <b>PCI-1802HU CR</b>   | Universal PCI, 44k S/s, 32-ch, 12-bit AI Multifunction Board (RoHS)<br>Includes one CA-4002 D-Sub connector |
| <b>PCI-1802HU/S CR</b> | Universal PCI, 44k S/s, 32-ch, 12-bit AI Multifunction Board (RoHS)<br>Includes one CA-3710 D-Sub cable     |

## Hardware Specifications

| Model                     | PCI-1802LU                                                                                                                                                                         | PCI-1802HU    |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| Hardware                  |                                                                                                                                                                                    |               |
| Card ID                   | Yes (4-bit)                                                                                                                                                                        |               |
| Connector                 | Female DB37 x 1 , Male 20-bit ribbon x 2                                                                                                                                           |               |
| Analog Input              |                                                                                                                                                                                    |               |
| Channels                  | 32 single-ended/16 differential                                                                                                                                                    |               |
| Range                     | Gain: 0.5, 1, 5, 10, 50, 100, 500, 1000<br>Bipolar Range: ±10 V, ±5 V, ±1 V, ±0.5 V, ±0.1V, ±0.05 V, ±0.01 V, ±0.005 V<br>Unipolar Range: 0 ~ 10 V, 0 ~ 1 V, 0 ~ 0.1 V, 0 ~ 0.01 V |               |
| Resolution                | 12-bit                                                                                                                                                                             |               |
| Accuracy                  | 0.01% of FSR ±1 LSB @ 25 °C, ±10 V                                                                                                                                                 |               |
| Sampling Rate             | 330 kS/s. Max.                                                                                                                                                                     | 44 kS/s. Max. |
| Input Impedance           | 10 MΩ/6 pF                                                                                                                                                                         |               |
| Overvoltage Protection    | Continuous ±35 Vp-p                                                                                                                                                                |               |
| Zero Drift                | ±2 ppm/°C of FSR                                                                                                                                                                   |               |
| FIFO Size                 | 8192 samples                                                                                                                                                                       |               |
| Trigger Mode              | Software, Internal programmable pacer, External (5 V/TTL)                                                                                                                          |               |
| Data Transfer             | Polling                                                                                                                                                                            |               |
| Analog Output             |                                                                                                                                                                                    |               |
| Channels                  | 2                                                                                                                                                                                  |               |
| Range                     | Bipolar:±5 V, ±10 V                                                                                                                                                                |               |
| Resolution                | 12-bit                                                                                                                                                                             |               |
| Accuracy                  | 0.06% of FSR ± 1 LSB @ 25 °C, ± 10 V                                                                                                                                               |               |
| Response Time             | 1.0 MHz (Typical)                                                                                                                                                                  |               |
| Voltage Output Capability | ±5 mA                                                                                                                                                                              |               |
| Slew Rate                 | 8.33 V/μs                                                                                                                                                                          |               |
| Operation Mode            | Static Update                                                                                                                                                                      |               |
| Digital Input             |                                                                                                                                                                                    |               |
| Channels                  | 16                                                                                                                                                                                 |               |
| Type                      | 5 V/TTL                                                                                                                                                                            |               |
| ON Voltage Level          | 2.0 V Min.                                                                                                                                                                         |               |
| OFF Voltage Level         | 0.8 V Max.                                                                                                                                                                         |               |
| Response Speed            | 1.0 MHz (Typical)                                                                                                                                                                  |               |
| Trigger Mode              | Static Update                                                                                                                                                                      |               |
| Digital Output            |                                                                                                                                                                                    |               |
| Channels                  | 16                                                                                                                                                                                 |               |
| Type                      | 5 V/TTL                                                                                                                                                                            |               |
| Operation Mode            | Static Update                                                                                                                                                                      |               |
| Load Voltage              | Logic 0: 0.4 V Max. , Logic 1: 2.4 V Min.                                                                                                                                          |               |
| Load Current              | Sink: 2.4 mA @ 0.8 V , Source: 0.8 mA @ 2.0 V                                                                                                                                      |               |
| Response Speed            | 1.0 MHz (Typical)                                                                                                                                                                  |               |
| Timer/Counter/Frequency   |                                                                                                                                                                                    |               |
| Channels                  | 3 (Independent x 1/Internal pacer x 1/External pacer x 1)                                                                                                                          |               |
| Type                      | 5 V/TTL                                                                                                                                                                            |               |
| Resolution                | 16-bit                                                                                                                                                                             |               |
| Input Frequency           | 10 MHz Max.                                                                                                                                                                        |               |
| Reference Clock           | Internal: 8 MHz                                                                                                                                                                    |               |
| PC Bus                    |                                                                                                                                                                                    |               |
| Type                      | 3.3 V/5 V Universal PCI , 32-bit, 33 MHz                                                                                                                                           |               |
| Data Bus                  | 16-bit                                                                                                                                                                             |               |
| Power                     |                                                                                                                                                                                    |               |
| Consumption               | 300 mA @ +5 V                                                                                                                                                                      |               |
| Mechanical                |                                                                                                                                                                                    |               |
| Dimensions (mm)           | 105 x 200 x 22 (W x L x D)                                                                                                                                                         |               |
| Environment               |                                                                                                                                                                                    |               |
| Operating Temperature     | 0 ~ +60°C                                                                                                                                                                          |               |
| Storage Temperature       | -20 ~ +70°C                                                                                                                                                                        |               |
| Humidity                  | 5 ~ 85% RH, Non-condensing                                                                                                                                                         |               |

## Accessories

|                                                                                     |                    |                                                                                |
|-------------------------------------------------------------------------------------|--------------------|--------------------------------------------------------------------------------|
|    | CA-2002 CR         | 20-pin flat cable, 20 cm x 2 (RoHS)                                            |
|    | CA-2010 CR         | 20-pin flat cable, 1 M (RoHS)                                                  |
|    | CA-2020 CR         | 20-pin flat cable, 2 M (RoHS)                                                  |
|    | CA-3710D CR        | DB-37 Male-Male D-sub cable 1 M (Cable for Daughter Board (180°)) (RoHS)       |
|    | CA-3715DM-H CR     | DB-37 Male-Male Cable, 1.5 M, 180° (RoHS)                                      |
|    | CA-3730DM-H CR     | DB-37 Male-Male Cable, 3.0 M, 180° (RoHS)                                      |
|    | DB-1825 CR         | Analog Input Screw terminal Board (RoHS)                                       |
|    | DB-8225 CR         | Screw terminal board , filter circuitry can be added for 1800HU, 1800LU (RoHS) |
|    | DB-889D CR         | 16-channel Analog Multiplexer Board (for PCI-1800LU/HU) (RoHS)                 |
|    | DB-16P CR          | 16-channel Isolated Digital Input Daughter Board (RoHS)                        |
|    | DB-16R CR          | 16-channel Relay Output Daughter Board (RoHS)                                  |
|   | DN-37 CR           | DIN Rail Mounting 37-pin Connector (RoHS)                                      |
|  | DN-20/DN-20-381 CR | 20-pin DIN-RAIL mounting I/O connector board (RoHS)                            |
|  | 2AB125R CR         | Resistor DIP 125R 0.1% 1/4W MF 50PPM (1PCS) (RoHS)                             |

### PCI-1802HU/PCI-1802LU PCI-1800HU/PCI-1800LU

